

Incredible **100,000 hrs**

GENERAL DESCRIPTION

Neptun's Auto Park Induction shoebox combines classic form and versatility to make it an excellent choice for new construction or retrofit applications. The 31 series shoebox fixture is offered in a variety of wattages. It can replace existing HID fixtures up to 400W.

APPLICATION

- Parking Lot Lighting
- Car Lot Lighting
- Area & Storage Lighting
- Street Lighting
- Walkway Lighting

STRUCTURE, MATERIALS, & FEATURES

- Heavy-gauge, die-cast aluminum housing.
- Custom designed anodized aluminum reflectors for superior illuminance.
- Heat and impact resistant tempered flat glass lens. (IESNA full-cutoff)
- Integral structural support plate for mounting arm ensures strength.
- Corrosion resistant electrocoat white finish (custom colors available).
- Hinged aluminum door frame incorporates external stainless steel latch.
- Inductively coupled circular induction bulb.
- High power factor, low THD electronic ballast with surge protection.
- Instant-On flicker-free Cold Start and Hot Re-Start.
- High quality glare-free light with high CRI above (83).
- Bright white light (5000°K) for greater visibility and safety.
- Advance phosphors for high lumen output and high lumen maintenance.
- Up to 20 year maintenance free operation.
- 10 Year Warranty.

ORDERING INFORMATION

Sample Number: 31080-UNV-850-LD-WHT
 Custom options and accessories available. Please consult factory

Series	Lamp Wattage	Voltage	Color Temp	Accessories	Color
31 = Auto-Park	080 = 80 W 100 = 100 W 120 = 120 W 150 = 150 W 200 = 200 W	UNV = Universal 480 = 480 V	830 = 3000°K 841 = 4100°K 850 = 5000°K * * Standard	LD = Light Sensor /Photocell	WHT = White * Custom Colors Available




PRODUCT INFORMATION

Model No.	Description	Rated Watts	Input Watts	Initial Lumens	Universal Line Voltage (VAC)	Max Line Current (Amp)	THD	Power Factor	Weight
31080	Large Auto-Park Fixture	80	82	6,400	120-277	0.69-0.30	<10%	0.98	25 lbs
31100	Large Auto-Park Fixture	100	105	8,000	120-277	0.87-0.37	<10%	0.98	25 lbs
31120	Large Auto-Park Fixture	120	126	9,600	120-277	1.05-0.45	<10%	0.98	27 lbs
31150	Large Auto-Park Fixture	150	158	12,000	120-277	1.31-0.56	<10%	0.98	28 lbs
31200	Large Auto-Park Fixture	200	210	16,000	120-277	1.75-0.75	<10%	0.98	28 lbs

SPECIFICATIONS


- Ballast Type Electronic
- Start Method InstantON
- Hot Re-start InstantON
- Universal Input Line Voltage 120-277 VAC
- Input Line Frequency 50/60 Hz
- Lamp Operating Frequency 250 kHz
- Ballast Off-State Draw 0 Watts
- Sound Rating Class A
- ANSI Surge Protection Class A
- Lamp / Ballast System Life 100,000 Hrs.
- Lumen Maintenance @75,000Hrs > 70%
- Color Temperature 5000°K
- Color Rendering Index (CRI) 83
- Minimum Starting Temperature -20°F
- Maximum Starting Temperature 160°F
- Initial Lumens per Watt 80
- Shock / Vibration Resistant Yes
- Power Factor > 0.98
- Total Harmonic Distortion < 10%
- Inrush Current Peak < 10 Amp
- ETL Listed / UL Standard 1598 Yes
- FCC Compliance Part 18, Subp. C
- EPA Rating 0.78
- IP Rating IP65
- Warranty 10 Year

DRILLING PATTERNS



Strait Arm Pole Mount Only

PHOTOMETRICS (See Complete IES File)



Type V Distribution