

Ledsion Lighting Technology Co., Ltd

LED HIGHBAY LIGHTS SERIES

Main Features

- CREE XML LED, high luminous efficiency and long life
- MEAN WELL high efficiency LED driver
- Universal voltage AC90-277V,AC347-528V available
- Fins cooling design, better cooling light quality, LED Tj<85℃
- Excellent optical design, greatly improve the light utilizati on and evenness.
- ETL、DLC、CE、RoHS certified
- 5years warranty

Model Number

LS-HHBC100W

LS-HHBC120W

LS-HHBC150W

LS-HHBC200W





























LS-HHBC100W LS-HHBC120W /150W LS-HHBC200W

Reflectors Available




Start you way of energy saving High quality LED lights Long lifespan Eco friendly

Luminous Intensity Distribution(C)



BeamAngle(50%):129.0 Deg BeamAngle(10%):147.0 Deg



Main Parameters

Model#	LS-HHBC100W	LS-HHBC120W	LS-HHBC150W	LS-HHBC200W
Power	100W	120W	150W	200W
Output Lumen	10000lm	12000lm	15000lm	20000lm
Certificate	ETL CE RoHS	ETL DLC CE RoHS DLC CE RoH		
Voltage	90~277VAC (180V-528VAC available)			
LED/Driver brand	CREE XML LED/MEAN WELL Driver			
Material of Heat sink	Die-casting aluminum			
Material of Diffuser Lens	Optical Glass			
ССТ	3000K-6500K			
Beam Angel	129Deg.(50%) 147Deg.(10%)			
PF	>0.9			
CRI	≥75			
IP Rating	IP65			
Color of heat sink and driver box available	Black and Silvery			
Working Temperature	-22°F~140°F/-30°C~60°C			
Lifespan	>50,000hrs			

Start you way of energy saving High quality LED lights Long lifespan Eco friendly

Model Number

LS-HHBC400W LS-HHBC500W LS-HHBC600W

































LS-HHBC400W










LS-HHBC500W/600W

Start you way of energy saving High quality LED lights Long lifespan Eco friendly

Luminous Intensity Distribution(C)



BeamAngle(50%):85.0 Deg BeamAngle(10%):105.0 Deg



Main Parameters

Model#	LS-HHBC400W	LS-HHBC500W	LS-HHBC600W		
Power	400W	500W	600W		
Output Lumen	36000lm	45000lm	54000lm		
Certificate	DLC CE RoHS				
Voltage	90~277VAC (180V-528VAC available)				
LED/Driver brand	CREE XML LED/MEAN WELL Driver				
Material	Die-casting aluminum				
CCT	3000K-6500K				
Beam Angel	85Deg.(50%) 105Deg.(10%)				
PF	>0.9				
CRI	≥75				
IP Rating	IP65 Outdoor use				
Working Temperature	-22 °F ~140°F/-30°C ~60°C				
Lifespan	>50,000hrs				

Start you way of energy saving

High quality LED lights

Long lifespan

Eco friendly

Applications

LED highbay lights are used in workshops, factories, warehouse, toll stations, gas stations, supermarket, exhibition halls, gymnasiums, etc..

