

. PRODUCT – IR4 SERIES

Class 1, Div 1 – Groups C & D Class 2, Div 1 & 2 – Groups E,F,G

Paint spray booth approved UL 844, 924 UL 1598 Marine Type NEMA 4X IP66

Nominal Length	Length Inches	Wie
2 FOOT 2 TUBE	27.5	11.2
4 FOOT 2 TUBE	52	11.2
4 FOOT 4 TUBE	52.5	24

SPECIFICATIONS

UL LISTING:

CLASS 1, DIVISION 1, GROUPS C & D

CLASS 2 , DIVISION 2 GROUPS E, F & G

UL 844 Hazardous Locations

UL 924 Emergency Lighting

UL 1598A Marine Outside Type

ABS

Construction

Corrosion resistant, marine grade, copper free aluminum, heavy gauge extruded reflectors with high gloss reflective finish

Hardware

stainless steel bolts

Lens

Explosion-proof, impact and heat resistant glass tubes, provide lamps protection

Light source

17W, 35W, 40W, 54W, 60W, LED

LED ARRAY-40 WATT EACH, 4000 NOMINAL LUMENS ON 4 FOOT STRIP

Power source

120-277v,50/60 Hz (UNV)

DRIVER-amp draw 120 volt-.80, 277 volt-.35

Ambient operating temperature

40°C maximum

Mounting

versatile mounting arrangement, standard end mounting and pendent mounting

Weight

2 foot 50.0 lbs

4 foot 60.0 lbs

4 foot, 4 lamp, 120 lbs.

Key features

Field replaceable led circuit boards and drivers with quick disconnects Convenient wiring access though screw-cap covers Factory sealed

Warranty

5 year warranty on LED



